

## SAE 0W-40 ACEA C3

### DESCRIPTION:

**SAE 0W-40 ACEA C3** is a fully synthetic engine oil utilizing mid-SAPs passenger car technology. It is designed for modern passenger diesel vehicles equipped with Diesel Particular Filter (DPF), and in latest gasoline applications, including the ones with 3-way catalytic converters.

### FEATURES/BENEFITS:

- Protects engines under all driving conditions
- Lowers friction and improves gas mileage
- Provides longer engine life
- Excellent high and low temperature performance
- Resists thermal break-down

### APPLICATIONS:

**SAE 0W-40 ACEA C3** is suitable for use in applications calling for of ACEA C3 and API SN/CF service categories. Can be used in light duty trucks and pick-up vehicles.

### Suitable for Use:

- ACEA C3
- API SN/CF
- Euro 6
- China 6

\* ALWAYS CONSULT YOUR OWNER'S MANUAL FOR THE PROPER FLUID FOR YOUR EQUIPMENT.

### TYPICAL TEST DATA

SAE GRADE	0W-40
Specific Gravity @ 60 °F	0.844
Viscosity, Kinematic cSt at 40°C	82.00
cSt at 100°C	14.38
Viscosity Index	183
CCS Vis, cP at -35°C, Max	6200
Flash Point, °F	460
Pour Point, °C (°F)	-30 (-22)
Color, Max	4.0
HTHS, cP at 150°C, Min	3.5

Typical test data are average values only. Minor variations which do not affect product performance are to be expected during normal manufacturing.