

SYNTHETIC DOT 4 HYDRAULIC BRAKE FLUID

DESCRIPTION:

SYNTHETIC DOT 4 HYDRAULIC BRAKE FLUID is a specially compounded preparation designed solely for use in motor vehicle braking systems. It is for use in all vehicles, where grade DOT 4 is recommended by manufactures. **SYNTHETIC DOT 4 HYDRAULIC BRAKE FLUID** far exceeds DOT 4 and other federal and SAE specifications for motor vehicle brake fluid. Mixes with all other approved brake fluids, and is suitable for use in ATE, Girling, Lockheed and other systems.

DIRECTIONS FOR USE:

- Follow vehicle manufacturer's recommendations when adding brake fluid.
- Keep brake fluid clean and dry. Contamination with dirt, water, petroleum products or other materials may result in brake faultier or costly repairs.
- Store brake fluid only in its original container. Keep container clean and tightly closed to prevent absorption of moisture.
- Do not refill container and do not use for other liquids.
- Avoid spilling on vehicle finish. If spilled, wipe off immediately with clean cloth.

APPLICATIONS:

SYNTHETIC DOT 4 HYDRAULIC BRAKE FLUID is a DOT 4 motor vehicle brake fluid for disc and drum brakes. It meets Federal Motor Vehicle Safety Standard No. 116, SAE J1704, and ISO 4925 (Class 4). It is certified by ABIC Testing Laboratories, Inc.

* ALWAYS CONSULT YOUR OWNER'S MANUAL FOR THE PROPER FLUID FOR YOUR EQUIPMENT.

Properties	Product Specifications
Specific Gravity @60°F	1.04 – 1.08
Dry Boiling Point, °F	475 Minimum
Wet Boiling Point, °F	311 Minimum
Color	Colorless to Amber

Typical test data are average values only. Minor variations which do not affect product performance are to be expected during normal manufacturing.